



3X Expansion



Obstructs Air



Quick Setting

MULTI-PURPOSE

Titebond® WeatherMaster™ X-TREME Multi-Purpose foam is a triple expansion, low pressure, one-component polyurethane foam sealant. It is moisture-cured and designed to seal and fill small cracks and voids. This product creates a tight barrier against noise, moisture and infiltration – even in X-TREME temperatures.

- **X-TREME TEMPERATURES 0° TO 100° F**
- **GREENGUARD GOLD CERTIFIED**
- **WON'T DRY OUT**
- **CREATES TIGHT BARRIER AGAINST NOISE, MOISTURE & AIR**
- **HIGH YIELD FORMULA**
- **3X THE EXPANSION**

SPECIFICATIONS

• ASTM D1622; ASTM C518; ASTM E2178; ASTM D1621; ASTM 1623; ASTM D2126; ASTM D6226; UL GREENGUARD GOLD; UL

PHYSICAL AND CHEMICAL CHARACTERISTICS:

Type: Low pressure, one component, polyurethane foam sealant

Flashpoint: -156° F (-68.9° C), estimated based on the liquefied petroleum gas (Hydrocarbon HC)

Freeze/Thaw Stability: Stable

Storage Life: 18 months

Reactive VOC: 165 g/L

Density: 1.10 lbs/ft³ (17.6 kg/m³)

K-Factor: 0.213 BTU · inch/ (ft² · h · °F)

R-Value: 4.70 per Inch

Air Barrier Properties: @1.57 psf (75 Pa)

Compressive Strength: 8.17 psi (56.2 kPa)

Tensile Strength: 12 psi (83 kPa)

Dimensional Stability: ± 5%

Closed-Cell Content: 67%

LIMITED WARRANTY: Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.



R38898 CAULKINGS AND SEALANTS
SURFACE BURNING CHARACTERISTICS APPLIED TO
INORGANIC REINFORCED CEMENT BOARD - 39P2
FLAME SPREAD: 25 SMOKE DEVELOPED: 50
Tested as applied in three 3/4" beads 5" OC covering 12.5%
of the exposed test sample area. The manufacturer makes the
following statement: The numerical flame spread rating is not
intended to reflect hazards by this or any other material
under actual fire conditions.

APPLICATION INSTRUCTIONS

24 oz. - Dispensing Unit only application method: Shake well, attach the container to X-TREME Dispensing Unit and begin dispensing. The Dispensing Unit can be metered by pulling the trigger for the desired rate, or with the metering screw located in the back. Foam application can be interrupted when needed as outlined in the instructions and the Dispensing Unit will be ready for immediate re-use, as long as it remains attached to a pressurized container. An empty gun foam container must be replaced with a new container.

12 oz. - Straw foam application method: Shake well, attach the straw, invert the container and begin dispensing. By activating the adapter lever carefully, the extrusion rate can be regulated.

Working Surfaces: Surfaces must be clean, dry, free of loose particles, and free of dust, grease, and mold release agents. It is the sole responsibility of the user to thoroughly test any proposed use with all substrates to determine project suitability prior to using product on your application.

LIMITATIONS

- This product is extremely flammable when dispensing.
- Carefully review cautions.
- Optimum temperature for use is between 65° - 80° F (18° - 27° C).
- Clean oil, dust and grease off surfaces to be foamed.
- Make sure to cover surrounding surfaces.
- Wear appropriate safety glasses, gloves and protective clothing. Consult SDS for product safety information.

For questions, please call our Help Line at 1.800.347.4583 or visit us at Titebond.com.

CAUTION STATEMENT

DANGER: Extremely flammable aerosol. Contains gas under pressure-may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause harm to breast-fed children. May cause respiratory irritation. May cause damage to organs through prolonged or repeat exposure. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing vapors or fumes. Do not get in eyes, on skin, or on clothing. Wash hands and other skin areas exposed to material thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, and eye protection. In case of inadequate ventilation, wear respiratory protection. **FIRST AID:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs, get medical attention. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if any and continue rinsing. If irritation persists: Get medical advice/attention. **FIRE:** In case of fire: Use water fog, foam, dry chemical, or carbon dioxide for extinction. Eliminate all ignition sources if safe to do so. Store in a well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50° C/122° F. Dispose of contents and container in accordance with applicable local, regional, national, or international regulations.

MULTI-PURPOSE

Product #	Size	Weight	UPC	Case UPC	Units Per Package	Packages Per Pallet
8521	12 oz.	14 lbs./Case	037083085211	10037083085218	12	75
8522	24 oz.	24 lbs./Case	037083085228	10037083085225	12	48

TITEBOND.COM



Franklin International

Sales: 1.800.669.4583 / Technical: 1.800.347.4583 ©2016 BCM 4/16 FF1035

