

COMPETITIVE COMPARISON GUIDE



Titebond
THE PRO'S ADVANTAGE

	WeatherMaster™ Ultimate MP™	Bostik 915	Chem Link™ DuraLink™ 50†	Dow Corning® 795†
PAINTABLE	Yes, 1 Hour (Except Translucent)	Yes, with latex-based paints once fully cured. Pretest to ensure compatibility.	Within 24 hours. Test and evaluate all paints before application.	No
% SOLIDS	100%	96%	100%	Not Stated
SHRINKAGE	0%	Not Stated	0%	Not Stated
JOINT FLEXIBILITY	50%	35%	50%	50%
VOC-COMPLIANT	<50 g/L	33.6 - 39.2 g/L	<22 g/L	32 g/L
GAP FILLING (WIDTH)	1"	1/2"	Up to 2"	Not Stated
COLD WEATHER EXTRUSION	0°F	Above 40°F	32°F	50°F
FOAMBOARD	Yes	Yes	Yes	Not Stated
ODOR / VAPOR	Very Mild	Solvent	Mild	Slight
OCCUPIED STRUCTURES	Yes	Use With Adequate Ventilation or Wear Mask	Yes	Yes; Only in a Well-ventilated Area
SERVICE TEMPERATURE	-75° to 212°F	-40° to 150°F	-40° to 200°F	-40° to 300°F
CARTRIDGE	Plastic (9.5 oz. Removable Nozzle) & 20 oz. Sausage Pack	Fiber (10.1 oz.) & 20 oz. Sausages	Plastic (10.1 oz. Fixed Nozzle), 20 oz. Sausages, 2 and 5 Gallon Pails or 50 Gallon Drums by Special Order	Plastic (10.3 oz.), 20 oz. Sausages, 2 Gallon and 4.5 Gallon Bulk Containers
WARRANTY	Limited	Limited	Limited	Limited
STANDARD COLORS	15+ Colors	10 Colors	12 Colors	15 Colors
CLASS	Class 50	Class 35	Class 50	Class 50
MANUFACTURED	Owned and Made in the USA	Not Stated	Not Stated	Not Stated
SHELF LIFE	24 Months	12 Months	12 Months, 6 Months for Pails	12 Months

MasterSeal® NP1™†	RainBuster® 850†	RainBuster® 975†	Sikaflex® 1a†	Tremco Dymonic® FC†	Vulkem® 116†
Yes, compatibility test required.	Yes, for best results, paint after 72 hours.	Yes, for best results, paint after 72 hours.	Yes, compatibility test required.	Yes, not stated.	Yes, not stated.
100%	96-99%	96-99%	Not Stated	100%	94%
0%	0%	0%	Not Stated	Not Stated	6%
35%	35%	35%	35%	35%	25%
35 g/L	VOC-compliant under AQMD & CARB	9 g/L	40 g/L	6 g/L	47 g/L
1 1/2"	1"	1"	1 1/2"	1/2"	1/2"
Only if substrates are completely dry, clean and free of moisture. Store at room temperature for 24 hours before using.	20°F. If below 40°F, condition product at 70°F prior to using for best results.	20°F. If below 40°F, condition product at 70°F prior to using for best results.	40°F. For cold weather application, condition units at approximately 70°F; remove prior to using.	Above 40°F	Above 40°F
Not Stated	Not Stated	Yes	Not Stated	Not Stated	Not Stated
Mild	Mild	Mild	Odorless	Mild	Mild
Ensure Adequate Ventilation	Yes; Only in a Well-ventilated Area	Not Stated	Yes; Use Only With Adequate Ventilation	Yes; Use Only With Adequate Ventilation	No
-40° to 180°F	Not Stated	-75° to 300°F (For Short Periods)	-40° to 170°F	-40° to 185°F	Not Stated
Fiber (10.1 oz. Fixed Nozzle) & 20 oz. ProPaks	Fiber (10.1 oz. Fixed Nozzle) & 20 oz. Sausages Tubes	Plastic (10.1 oz. Fixed Nozzle)	Fiber (10.1 oz. Fixed Nozzle) 20 oz. Uni-Pac Sausages, 5 Gallon Pails & 55 Gallon Drums	Fiber (10.1 oz. Fixed Nozzle), & 20 oz. Sausages	Fiber (10.1 oz. Fixed Nozzle), 20 oz. Sausages, 2 Gallon Pails, 5 Gallon Pails & 55 Gallon Drums
Limited	Lifetime	Lifetime	1 Year	Tremco warrants its products to be free of defects in materials, but makes no warranty to appearance or color. Replace or refund.	Tremco warrants its products to be free of defects in materials, but makes no warranty to appearance or color. Replace or refund.
11 Colors	6 Colors	7 Colors	9 Colors	18 Colors	16 Colors
Class 35	Class 35	Class 35	Class 35	Class 35	Class 25
Not Stated	Not Stated	Not Stated	Not Stated	USA & Canada	USA & Canada
12 Months	12 Months	12 Months	12 Months, 6 Months for Pails & Drum	Not Stated	Not Stated



IDEAL FOR ▶ Window / Doors / Shutters / Exterior Trim / Metal Siding / Vinyl Siding / General Roofing Applications / Gutters / Vents / RV, Tractor Trailers & Buses

ULTRA LOW VOC ▶ VOC-compliant in all 50 states

JOINT MOVEMENT CAPABILITY ± 50% ▶ Remains permanently flexible

WEATHER & UV RESISTANT ▶ Produces long-lasting weather-tight seals

ALL-WEATHER APPLICATION ▶ Suitable for all climates

PAINTABLE ▶ Painting may occur one hour after application with a water-based (latex-based) paint.

Provided information obtained from manufacturer's product labels, technical data sheets and SDS.

* Titebond WeatherMaster ULTIMATE MP Translucent (#71111) is NOT paintable.

† ChemLink and Duralink are trademarks of Chem Link; Dow Corning is a registered trademark of Dow Corning Corporation; MasterSeal is a registered trademark and NP1 is a trademark of BASF; RainBuster is a registered trademark of Top Industrial, Inc.; Sikaflex is a registered trademark of Sika; Dymonic and Vulkem are registered trademarks of Tremco, Inc.

‡ Maximum temperature over 200°F is for short term exposures.

Visit Titebond.com for the most up-to-date product information.

Franklin International



Columbus, Ohio 43207 614.443.0241 Technical Service 1.800.347.4583 © 2020 01539_4797N FF1101

Titebond
THE PRO'S ADVANTAGE